

ra Rubber & Accessories

Your Hose and Belting Resource

Lakeland, FL - 800-282-1734 / Tucker, GA - 800-647-3743



O-RINGS

70 DUROMETER BUNA-N

O-RINGS: The o-ring is the most widely used seal in industry today. It is simple in concept, easy to install, can be used as a double-acting seal, can seal pressure to over 5,000 PSI in static and dynamic applications and, best of all, is very economical. While simple in concept, it can be very sophisticated in its application. An extensive range of sizes and compounds of o-rings are available from stock or we will fabricate your special engagement. O-ring kits are also available offering a wide range of standard sizes.

.070" WIDTH

SIZE	PRODUCT CODE	I.D.	WIDTH	SIZE	PRODUCT CODE	I.D.	WIDTH
001	22001	.029	.040	026	22026	1.239	.070
002	22002	.042	.050	027	22027	1.301	.070
003	22003	.056	.060	028	22028	1.364	.070
004	22004	.070	.070	029	22029	1.489	.070
005	22005	.101	.070	030	22030	1.614	.070
006	22006	.114	.070	031	22031	1.739	.070
007	22007	.145	.070	032	22032	1.864	.070
008	22008	.176	.070	033	22033	1.989	.070
009	22009	.208	.070	034	22034	2.114	.070
010	22010	.239	.070	035	22035	2.239	.070
011	22011	.301	.070	036	22036	2.364	.070
012	22012	.364	.070	037	22037	2.489	.070
013	22013	.426	.070	038	22038	2.614	.070
014	22014	.489	.070	039	22039	2.739	.070
015	22015	.551	.070	040	22040	2.864	.070
016	22016	.614	.070	041	22041	2.989	.070
017	22017	.676	.070	042	22042	3.239	.070
018	22018	.739	.070	043	22043	3.489	.070

019	22019	.801	.070	044	22044	3.739	.070
020	22020	.864	.070	045	22045	3.989	.070
021	22021	.926	.070	046	22046	4.239	.070
022	22022	.989	.070	047	22047	4.489	.070
023	22023	1.051	.070	048	22048	4.739	.070
024	22024	1.114	.070	049	22049	4.989	.070
025	22025	1.176	.070	050	22050	5.239	.070

[Previous Page](#) || [View PDF of O-Rings](#) 

ra Rubber & Accessories

Your Hose and Belting Resource

Lakeland, FL - 800-282-1734 / Tucker, GA - 800-647-3743



F - RINGS

O-RINGS: The o-ring is the most widely used seal in industry today. It is simple in concept, easy to install, can be used as a double-acting seal, can seal pressure to over 5,000 PSI in static and dynamic applications and, best of all, is very economical. While simple in concept, it can be very sophisticated in its application. An extensive range of sizes and compounds of o-rings are available from stock or we will fabricate your special engagement. O-ring kits are also available offering a wide range of standard sizes.

.103" WIDTH

SIZE	PRODUCT CODE	I.D.	WIDTH
102	22051	.049	.103
103	22052	.081	.103
104	22053	.112	.103
105	22054	.143	.103
106	22055	.174	.103
107	22056	.206	.103
108	22057	.237	.103
109	22058	.299	.103
110	22059	.362	.103
111	22060	.424	.103
112	22061	.487	.103
113	22062	.5849	.103
114	22063	.612	.103
115	22064	.674	.103
116	22065	.737	.103
117	22066	.799	.103
118	22067	.862	.103
119	22068	.924	.103
120	22069	.987	.103
121	22070	1.049	.103

122	22071	1.112	.103
123	22072	1.174	.103
124	22073	1.237	.103
125	22074	1.299	.103
126	22075	1.362	.103
127	22076	1.424	.103
128	22077	1.487	.103
129	22078	1.549	.103
130	22079	1.612	.103
131	22080	1.674	.103
132	22081	1.737	.103
133	22082	1.799	.103
134	22083	1.862	.103
135	22084	1.925	.103
136	22085	1.987	.103
137	22086	2.050	.103
138	22087	2.112	.103
139	22088	2.175	.103
140	22089	2.237	.103
141	22090	2.300	.103
142	22091	2.362	.103
143	22092	2.425	.103
144	22093	2.487	.103
145	22094	2.550	.103
146	22095	2.612	.103
147	22096	2.675	.103
148	22097	2.737	.103
149	22098	2.800	.103
150	22099	2.862	.103
151	22100	2.987	.103
152	22101	3.237	.103
153	22102	3.487	.103
154	22103	3.737	.103
155	22104	3.987	.103
156	22105	4.237	.103
157	22106	4.487	.103
158	22107	4.737	.103
159	22108	4.987	.103
160	22109	5.237	.103
161	22110	5.487	.103
162	22111	5.737	.103
163	22112	5.987	.103

164	22113	6.237	.103
165	22114	6.487	.103
166	22115	6.737	.103
167	22116	6.987	.103
168	22117	7.237	.103
169	22118	7.487	.103
170	22119	7.737	.103
171	22120	7.987	.103
172	22121	8.237	.103
173	22122	8.487	.103
174	22123	8.737	.103
175	22124	8.987	.103
176	22125	9.237	.103
177	22126	9.487	.103
178	22127	9.737	.103

[Previous Page](#) || [View PDF of O-Rings](#) 

ra Rubber & Accessories

Your Hose and Belting Resource

Lakeland, FL - 800-282-1734 / Tucker, GA - 800-647-3743



O-RINGS

O-RINGS: The o-ring is the most widely used seal in industry today. It is simple in concept, easy to install, can be used as a double-acting seal, can seal pressure to over 5,000 PSI in static and dynamic applications and, best of all, is very economical. While simple in concept, it can be very sophisticated in its application. An extensive range of sizes and compounds of o-rings are available from stock or we will fabricate your special engagement. O-ring kits are also available offering a wide range of standard sizes.

.139" WIDTH

SIZE	PRODUCT CODE	I.D.	WIDTH
201	22128	.171	.139
202	22129	.234	.139
203	22130	.296	.139
204	22131	.359	.139
205	22132	.421	.139
206	22133	.484	.139
207	22134	.546	.139
208	22135	.609	.139
209	22136	.671	.139
210	22137	.734	.139
211	22138	.796	.139
212	22139	.859	.139
213	22140	.921	.139
214	22141	.984	.139
215	22142	1.046	.139
216	22143	1.109	.139
217	22144	1.171	.139
218	22145	1.234	.139
219	22146	1.296	.139
220	22147	1.359	.139

221	22148	1.421	.139
222	22149	1.484	.139
223	22150	1.609	.139
224	22151	1.734	.139
225	22152	1.859	.139
226	22153	1.984	.139
227	22154	2.109	.139
228	22155	2.234	.139
229	22156	2.359	.139
230	22157	2.484	.139
231	22158	2.609	.139
232	22159	2.734	.139
233	22160	2.859	.139
234	22161	2.984	.139
235	22162	3.109	.139
236	22163	3.234	.139
237	22164	3.359	.139
238	22165	3.484	.139
239	22166	3.609	.139
240	22167	3.734	.139
241	22168	3.859	.139
242	22169	3.984	.139
243	22170	4.109	.139
244	22171	4.234	.139
245	22172	4.359	.139
246	22173	4.484	.139
247	22174	4.609	.139
248	22175	4.734	.139
249	22176	4.859	.139
250	22177	4.984	.139
251	22178	5.109	.139
252	22179	5.234	.139
253	22180	5.359	.139
254	22181	5.484	.139
255	22182	5.609	.139
256	22183	5.734	.139
257	22184	5.859	.139
258	22185	5.984	.139
259	22186	6.234	.139
260	22187	6.484	.139
261	22188	6.734	.139
262	22189	6.984	.139

263	22190	7.234	.139
264	22191	7.484	.139
265	22192	7.734	.139
266	22193	7.984	.139
267	22194	8.234	.139
268	22195	8.484	.139
269	22196	8.734	.139
270	22197	8.984	.139
271	22198	9.234	.139
272	22199	9.484	.139
273	22200	9.734	.139
274	22201	9.984	.139
275	22202	10.484	.139
276	22203	10.984	.139
277	22204	11.484	.139
278	22205	11.984	.139
279	22206	12.984	.139
280	22207	13.984	.139
281	22208	14.984	.139
282	22209	15.955	.139
283	22210	16.955	.139
284	22211	17.955	.139

[Previous Page](#) || [View PDF of O-Rings](#) 

ra Rubber & Accessories

Your Hose and Belting Resource

Lakeland, FL - 800-282-1734 / Tucker, GA - 800-647-3743



F-RINGS

O-RINGS: The o-ring is the most widely used seal in industry today. It is simple in concept, easy to install, can be used as a double-acting seal, can seal pressure to over 5,000 PSI in static and dynamic applications and, best of all, is very economical. While simple in concept, it can be very sophisticated in its application. An extensive range of sizes and compounds of o-rings are available from stock or we will fabricate your special engagement. O-ring kits are also available offering a wide range of standard sizes.

.210" WIDTH

SIZE	PRODUCT CODE	I.D.	WIDTH
309	22212	.412	.210
310	22213	.475	.210
311	22214	.537	.210
312	22215	.600	.210
313	22216	.662	.210
314	22217	.725	.210
315	22218	.787	.210
316	22219	.850	.210
317	22220	.912	.210
318	22221	.975	.210
319	22222	1.037	.210
320	22223	1.100	.210
321	22224	1.162	.210
322	22225	1.225	.210
323	22226	1.287	.210
324	22227	1.350	.210
325	22228	1.475	.210
326	22229	1.600	.210
327	22230	1.725	.210
328	22231	1.850	.210

329	22232	1.975	.210
330	22233	2.100	.210
331	22234	2.225	.210
332	22235	2.350	.210
333	22236	2.475	.210
334	22237	2.600	.210
335	22238	2.725	.210
336	22239	2.850	.210
337	22240	2.975	.210
338	22241	3.100	.210
339	22242	3.225	.210
340	22243	3.350	.210
341	22244	3.475	.210
342	22245	3.600	.210
343	22246	3.725	.210
344	22247	3.850	.210
345	22248	3.975	.210
346	22249	4.100	.210
347	22250	4.225	.210
348	22251	4.350	.210
349	22252	4.475	.210
350	22253	4.600	.210
351	22254	4.725	.210
352	22255	4.850	.210
353	22256	4.975	.210
354	22257	5.100	.210
355	22258	5.225	.210
356	22259	5.350	.210
357	22260	5.475	.210
358	22261	5.600	.210
359	22262	5.725	.210
360	22263	5.850	.210
361	22264	5.975	.210
362	22265	6.225	.210
363	22266	6.475	.210
364	22267	6.725	.210
365	22268	6.975	.210
366	22269	7.225	.210
367	22270	7.475	.210
368	22271	7.725	.210
369	22272	7.975	.210
370	22273	8.225	.210

371	22274	8.475	.210
372	22275	8.725	.210
373	22276	8.975	.210
374	22277	9.225	.210
375	22278	9.475	.210
376	22279	9.725	.210
377	22280	9.975	.210
378	22281	10.475	.210
379	22282	10.975	.210
380	22283	11.475	.210
381	22284	11.975	.210
382	22285	12.975	.210
383	22286	13.975	.210
384	22287	14.975	.210
385	22288	15.955	.210
386	22289	16.955	.210
387	22290	17.955	.210
388	22291	18.955	.210
389	22292	19.955	.210
390	22293	20.955	.210
391	22294	21.955	.210
392	22295	22.940	.210
393	22296	23.940	.210
394	22297	24.940	.210
395	22298	25.940	.210

[Previous Page](#) || [View PDF of O-Rings](#) 

ra Rubber & Accessories

Your Hose and Belting Resource

Lakeland, FL - 800-282-1734 / Tucker, GA - 800-647-3743



O-RINGS

O-RINGS: The o-ring is the most widely used seal in industry today. It is simple in concept, easy to install, can be used as a double-acting seal, can seal pressure to over 5,000 PSI in static and dynamic applications and, best of all, is very economical. While simple in concept, it can be very sophisticated in its application. An extensive range of sizes and compounds of o-rings are available from stock or we will fabricate your special engagement. O-ring kits are also available offering a wide range of standard sizes.

.275" WIDTH

SIZE	PRODUCT CODE	I.D.	WIDTH
425	22299	4.475	.275
426	22300	4.600	.275
427	22301	4.725	.275
428	22302	4.850	.275
429	22303	4.975	.275
430	22304	5.100	.275
431	22305	5.225	.275
432	22306	5.350	.275
433	22307	5.475	.275
434	22308	5.600	.275
435	22309	5.725	.275
436	22310	5.580	.275
437	22311	5.975	.275
438	22312	6.225	.275
439	22313	6.475	.275
440	22314	6.725	.275
441	22315	6.975	.275
442	22316	7.225	.275
443	22317	7.475	.275
444	22318	7.725	.275

445	2319	7.975	.275
446	22320	8.475	.275
447	22321	8.975	.275
448	22322	9.475	.275
449	22323	9.975	.275
450	22324	10.475	.275
451	22325	10.975	.275
452	22326	11.475	.275
453	22327	11.975	.275
454	22328	12.475	.275
455	22329	12.975	.275
456	22330	13.475	.275
457	22331	12.975	.275
458	22332	14.475	.275
459	22333	14.975	.275
460	22334	15.475	.275
461	22335	15.955	.275
462	22336	16.455	.275
463	22337	16.955	.275
464	22338	17.455	.275
465	22339	17.955	.275
466	22340	18.455	.275
467	22341	18.955	.275
468	22342	19.455	.275
469	22343	19.955	.275
470	22344	20.955	.275
471	22345	21.955	.275
472	22346	22.940	.275
473	22347	23.940	.275
474	22348	24.940	.275
475	22349	25.940	.275

[Previous Page](#) || [View PDF of O-Rings](#) 

ra Rubber & Accessories

Your Hose and Belting Resource

Lakeland, FL - 800-282-1734 / Tucker, GA - 800-647-3743



O-RINGS MISCELLANEOUS PARTS

BUNA-N O-RING CORD STOCK

SIZE	PRODUCT CODE
.070	22369
.103	22370
.139	22371
.210	22372
.275	22373
.375	22374
.500	22368

O-RING KITS

COMPOUND	PRODUCT CODE
Buna-N	22377
Viton	22378

O-RING SPLICE KITS

COMPOUND	PRODUCT CODE
Buna-N (Standard)	22376
Buna-N (Metric)	22380

PARKER O-RING GAUGE

PRODUCT CODE
22375

ra Rubber & Accessories

Your Hose and Belting Resource

Lakeland, FL - 800-282-1734 / Tucker, GA - 800-647-3743



OUR MISSION

is to continue to build our business on the solid foundation of ethics, service and reliability.

OUR INTENTION

is to profit, but only in such a manner as to be compatible with these guidelines.

Our combined years of experience in the industrial rubber industry is substantial and because of this we feel uniquely qualified and deeply honored to serve the industrial rubber needs of our customers.

TERMS AND CONDITIONS

- Payment: Net 30 days, subject to credit approval. Discounts improperly taken will be charged back. A service charge of 1½% per month will be made on all delinquent accounts.
- Freight: Full freight allowed on orders of \$2,500 net or more to one destination East of the Mississippi
- Prices: Subject to change without notice.
- Warranty: All products are guaranteed against defective material and/or workmanship. Warranty or guarantee is limited to the purchase of merchandise only.
- Credit: Permission must be granted before any merchandise can be returned for credit. A return Authorization Number must accompany all returned merchandise.

MAILING ADDRESS

FLORIDA

Warehouse / Sales Office

2120 Edgewood Drive So.
Lakeland, FL 33803

GEORGIA

Warehouse / Sales Office
4754-F. N. Royal Atlanta Dr.
Tucker, GA 30084

Remit to:

P.O. Box 777
Eaton Park, FL 33840

PHONE

lakeland office/warehouse

Local: 863-665-6115
Fax: 863-665-4540
Toll Free: 800-282-1734

atlanta office/warehouse

Local: 770-934-6062
Fax: 770-934-9024
Toll Free: 800-647-3743

Copyright 2009 - by Rubber & Accessories, Inc. All rights reserved. No part of this catalog may be reproduced or transmitted in any form or by any means, electronic or mechanical, including, but not limited to, photocopy, recording or information storage without permission in writing from the publisher.

Rubber & Accessories, Inc. | Lakeland, FL - 800-282-1734 | |Tucker, GA - Phone: 800-647-3743 | Email: [INFO](#)